

LINE INTERACTIVE UPS

UPS NT-V525A-DA



Main features:

- CPU controlled
- Auto re-starts when AC recovers
- Silence setup
- Automatic charging (offline charging)
- Battery low voltage protection
- Overload & short circuit protection
- Wide input voltage range

TECHNICAL SPECIFICATION

MODEL	NT-V525A-DA	
Capacity	500VA/300W	
Input	Voltage	110/120Vac or 220/230/240Vac
	Voltage range	85-150Vac / 165-265Vac
	Frequency range	46-54Hz
Output	Voltage	110/120 VAC or 220/230/240 VAC \pm 10%
	Frequency range	60 \pm 1Hz or 50 \pm 1Hz (Battery mode)
	Transfer time	Typical 2-6ms. 10ms max
	Wave form	PWM (Bat,mode)
Battery	Battery model & Quantity	12V/4.5AH X 1
	Charge period	4-6 hours recover to 90% capacity
	Backup time	(Halfload or 150W): 6 minutes
Protection	Full protection: Low voltage, overload & short circuit protection	
Physical	Unit dimension(mm)	255*98*140
	Net weight(kg)	3.6
Environment	Environment of performance	Temperalure 0°C-40°C, Humidity 20%-90%
	Noise level	\leq 40dB(1m)
Management	LCD or LED, RJ45/11 & USB (optional)	